



Ballast 12 Volt DC

- Product advantages**

 - ▶ Short-circuit-proof
 - ▶ Overload-protected
 - ▶ Temperature-protected
- Application**

 - ▶ For 12 Volt DC furniture lights
- Order information**

 - ▶ Select ballast according to the power consumption (watts) of the luminaires
- Features**

 - ▶ Combination with PWM dimmers possible secondarily

Technical details



Surface finish: White
Operating voltage: 200-240 Volt AC
Mains frequency: 50/60Hz
Output voltage: 12 Volt DC
Test marks and symbols:   
Protection rating: IP20 / IP44
Supply lead: 2000 mm
Primary connector: Euroflat
Standby: < 0.5W
Secondary connector: Mini connector M1

Ballast 12 Volt DC

Ballast 6 W with Euro flat plug (1-way)	30 226 02
Ballast 20 W with Euro flat plug (6-way distributor)	31 016 01
Ballast 30 W with Euro flat plug (1-way + 6-way distributor)	31 002 07
IP 44 ballast 30 W with Euro flat plug (6-way distributor)	31 018 01
Ballast 40 W with Euro flat plug (6-way distributor)	30 488 12
Ballast 60 W with Euro flat plug (9-way distributor)	31 025 01

Assembly drawing

